5

10

DT09 Rec'd PCT/PT0 2 1 DEC 2004 PCT/US2003/019410



System and Method for Noninvasive Diagnostic Imaging, Detection, and Identification of
Substances by Microwave/RF Modulation of X-rays and Applications in Treatment of
Diseases Characterized by the Presence of Pathological Macromolecules or by the Need
for Regeneration of Normal Tissue

BACKGROUND OF THE INVENTION

Related Applications

The present application claims the benefit of provisional patent applications "System and Method for Imaging Macromolecules," serial number 60/390,768, filed 6/21/2002, "System and Method for Imaging Macromolecules, serial number 60/390,995, filed 6/24/2002, and "System and Method for Regeneration of Cells and Tissues", serial number 60/391,351, filed 6/25/2002.

Field of Invention

The present invention relates generally to the field of radiotherapy treatment systems.

5 More specifically, the present invention is related to application of modulated x-rays.

Discussion of Prior Art

U.S. Patent No. 5,044,006, entitled MICROWAVE FREQUENCY MODULATION

OF X-RAY BEAM FOR RADIO THERAPY TREATMENT SYSTEM, commonly invented (Cyrulnik), issued on August 27, 1991, and hereby incorporated by reference, discloses a method and apparatus for producing an x-ray beam modulated at a microwave frequency for absorption by pathological materials including

11162644.01

BEST AVAILABLE COFY

macromolecules, such as oncogenes, for the radiological therapeutic treatment of tumors and other pathological conditions. As disclosed by Cyrulnik, the atomic structure of certain macromolecules (molecules having a backbone structure of 20,000 or more atoms) suggests that such molecules may have a "signature" frequency for resonant energy absorption. In the system of Cyrulnik, an x-ray beam is amplitude modulated at a predetermined or empirically determined microwave frequency equal to a resonant interactive frequency for a selected pathological material. Sufficient x-ray energy may be supplied, for example, in order to destroy the pathological material.

10

The teachings of the 5,044,006 patent are best understood with the following discussion of the technology in conjunction with original figures 2 and 6 of the '006 patent (herein figures 1 and 2):

1. Molecular Orbitals

15

The energy of an electron in orbit must be sufficient to counterbalance the attracting electromagnetic force maintaining it in orbit, which, like gravitational force, varies inversely with the square of its distance to the center of attraction, that is, the size of the orbit. The energy absorbed in a transition between adjacent orbitals therefore varies inversely with the difference in the squares of these distances, which are close to each other in value being adjacent:

$$a^2 - b^2 = (a-b)(a+b)$$

WO 2004/000414 PCT/US2003/019410 3

which approximates a constant x a, so that the energy absorbed is inversely proportional

to the size of the orbital.

2. <u>DNA</u>

5

Deoxyribonucleic acid, the genetic material of which the chromosomes of human cells

are composed, consists of pairs of macromolecules containing a backbone of units of 5

carbon atoms linked by phosphorous and oxygen atoms and each with a side chain of a

purine or pyrimidine base. Viruses and genes that cause cancer (oncogenes) consist of

such macromolecules with lengths on the order of 4,000 base pairs, or a backbone of

some 20,000 atoms.

3. Resonant Frequency

The lowest transitions of electron orbitals in single atoms result in absorption of visible

light, which has a frequency about 4(10 14) cycles per second (cps). As previously

explained, and as can be shown rigorously, the frequency of absorption by the lowest

transition of molecular orbitals varies inversely with the size of the molecule.

A molecule 20,000 base pairs in length, each containing a string of 8 atoms per set of

exons and introns, would therefore be expected to absorb radiation at a frequency of:

 $[1/(8 \cdot 2)](1/2 \cdot 10^4)(4 \cdot 10^{14})=4/32 \cdot 10^{10}$

 $=1.25 \cdot 10^9 \text{ cps}$

11162644.01

which is in the microwave range.

4. Penetration by Modulation

5

The principle used extensively in radio and television transmission of modulating a carrier wave by one of considerable different frequency can be utilized to overcome the difficulty of delivering selectively-absorbable radiation with destructive potential to oncogenes. When the carrier wave is modulated by a signal containing a square wave component such as occurs when it is generated by a device that is turned on and off at the modulating frequency, then radiation with components at both frequencies results, so that resonant absorption of the compound carrier wave can take place. In this way, if an x-ray beam is turned on and off at a resonant microwave frequency, it can act as a carrier wave to allow penetration of the microwave frequency energy to its otherwise inaccessible target, and at the same time be selectively absorbed by macromolecules such as oncogenes whose resonant frequency of absorption is tuned to the frequency of modulation of the x-ray beam by the microwave frequency.

This can be accomplished by interposing a klystron or similar device in the high voltage circuit of the x-ray generating tube, which will turn the beam on and off at microwave frequencies.

5. Detection

11162644.01

WO 2004/000414 PCT/US2003/019410 5

To determine when absorption is occurring and by which structures without having to empirically destroy tissue by trial and error, modulate the x-ray beam of a CAT scanner with a klystron or similar device. A CAT scanner detects the absorption of a standard low radiation level diagnostic x-ray beam at any point inside the body by dividing that beam so that it is viewed from several angles.

If this is done over the spectrum of frequencies of possible absorption by oncogenes, then at those frequencies which are absorbed by the genetic material unique to the tumor or malignancy, that tissue, and that tissue alone, will show up as absorbent on the scan.

10

The spectrum of microwave frequencies can be impressed on the scanner's x-ray beam at each angle during the course of a single scan by systematically varying the klystron frequency. Since absorption occurs in 10^{-9} seconds, the electron beam, which has a single target dwell time of 100 microseconds, can accommodate $10^{-4}/10^{-9} = 10^{5}$ different microwave frequencies of modulation. Thus, each of the 30,000 or so human genes could be tested for unique absorption at 3 frequencies in one scan, allowing for allelic mutation.

A scan would be generated from memory for each frequency by sampling the detector output at any particular time delay after the initiation of the beam. Each absorbing structure, such a tumor, would "light up" when its resonant frequency is selected.

Although only a small portion of the x-ray beam is utilized at any given modulating frequency, this is sufficient to produce the same intensity of absorption as is seen on an ordinary CAT scan, as will be shown in the next section.

6. Safety

In an ordinary plain skull x-ray series (which contains the same dose of radiation as a CT scan), approximately 3% of the x-ray beam is absorbed in total, of which the brain absorbs 1%. This 3/10,000 of the beam is absorbed by a column of cells given by the cube root of the number of cells in the roughly spherical brain, which total 3(10¹⁰), their cube root being about 3000.

If, instead of the type of absorption seen in a spectrophotometer where each subsequent unit absorbs the same proportion of the beam, the entire beam is absorbed by a single cell, then in order to absorb the same amount of radiation as in an ordinary CT scan (and thus in an ordinary skull x-ray), a single cell would have to absorb 1/3000 of the 3/10,000 of the beam which is 1/10⁷. The duty cycle of modulation limits to this maximum the absorbable radiation at each frequency of modulation of the x-ray beam during imaging.

Therefore, even though each resonant cell absorbs the entire available beam at that frequency, it absorbs no more than would be absorbed from an ordinary plain film, yet it absorbs 3000 times as much as other cells and 30 times as much as bone, allowing safe but effective detection by CT.

7. Treatment

7

Once the unique frequency of absorption of the modulated x-ray beam has been determined as noted above, selective destruction of undesirable structures such as oncogenes or their RNA transcripts, viruses, or other macromolecular nucleic acid configurations can be accomplished by scanning the patient a second time, this time with the klystron tuned to the unique resonant frequency of absorption throughout the duration of the x-ray beam. In this way the duty cycle during absorption is increased by a factor of approximately 109. (Before, it was turned on 109 times per second, each time at a different frequency; now each of the 109 times occurs at the single unique resonant absorbed frequency). Even if every cell of one of the several cell types in the brain were malignant, the increased dosage at full duty cycle of a factor of 109 of radiation specifically to those cells, each absorbing 3000 times the radiation that it would in a conventional skull x-ray series or CT scan, would be sufficient to eliminate or deimmortalize them all. In practice, a tumor becomes symptomatic at a cell volume of approximately 10⁵ cells, so that the effective dosage delivered to such a tumor would be equivalent to $3000(10^9)(10^{-5}) = 3(10^7)$ rads per cell (the total radiation dose in a CAT scan being on the order of a rad), which is 3000 times the curative maximum dosage used in radiotherapy, with the significant difference being that in this case the dosage delivered to the rest (nonmalignant) of the cells which do not absorb is still only one additional rad for this second scan, so that the treatment would be safe to normal cells.

In conventional radiation therapy, however, lethal tumor dose of 5000 rads represents a total, each cell only absorbing 1/10⁵ of this (or, in the case of neoplastic cells a somewhat greater multiple of the same order of magnitude) i.e. about 1/10 of a rad. With the proposed technique, this can be multiplied 10⁵ fold, which would easily destroy the tumor, even if repair is allowed for. Fractionation of the 5000 rads into 200 rad doses to

WO 2004/000414 PCT/US2003/019410

minimize radiation damage to other tissues can be obviated, minimizing repair of the tumor cells.

The net lethal effect on target tissue of the proposed technique is on the order of 100 times that of conventional radiotherapy, whereas radiation exposure of nontargeted tissue is 3000 times less than a diagnostic x-ray series.

Of course, with the disclosed technique the dose can also be fractionated by reducing the duty cycle if 100 times the lethal tumor dose is not needed, depending on the clinical situation such as the size of the tumor. Higher doses can also be achieved if desired by repeating the scan at full duty cycle, each repetition doubling the dose to the malignancy with negligible additional radiation to healthy tissue. Furthermore, once the unique frequency of resonant absorption is determined using the CT scanner, the klystron or other modulating device can be connected to conventional x-ray equipment, whether a simple diagnostic x-ray tube or radiotherapy equipment, in order to modulate its beam so as to achieve a more rapid treatment session than with a CAT scanner.

It should be noted that, unlike other techniques which selectively target tissue in a spatial manner by limiting radiation to a small area at the site of the tumor, the disclosed technique, though highly selective against undesirable tissue, is not limited in space, and can thus destroy those malignant cells outside the main tumor bulk which are responsible for recurrence, failed surgery, and metastasis. In principle, LY.H. this technique could be used in a total body fashion to cure metastatic malignancy because of its high selectivity and consequent high safety factor and effectiveness.

Furthermore, since the detection process is empirical, determining solely which frequency is uniquely absorbed by the malignancy, it does not depend on the cause(s) of cancer; as long as there is an abnormal genetic configuration unique to the tumor, even if it also involves loss of inhibition by an inactivated or abnormally absent gene, the change in that length of the DNA molecule being transcribed by the chromosome should result in a

unique pattern of absorption with consequent destruction of the tumor by the radiation.

8. Equipment

- Disclosed is the concept of producing selective elimination of undesirable entities by achieving resonant absorption of penetrating radiation by their macromolecules of specific configuration, such as oncogenes and viruses, by means of modulation of the radiation at that resonant frequency whose unique absorption is determined in a safe manner using computerized tomography (CT). The method of achieving unique absorption of high energy radiation by modulating at the resonant frequency was an innovation in this proposal, as is its application in the treatment of malignancy, including determining, in a unique manner, the frequency of modulation resulting in absorption empirically but safely using CT.
- The equipment itself consists of a CT scanner and a klystron microwave device, both of established safety and effectiveness. Guidelines for use have also been established including shielding requirements. (The current proposal would not change the penetrating characteristics of the radiation, so that these operating characteristics would still pertain, in particular as regards shielding, which again, are well established.) As the

above analysis shows, the proposed combination of these devices exhibits enhanced effectiveness at no cost to safety.

FIG. 1 (figure 1 of *006 patent) shows a radiating system 20 including a CT scanner 22 which has been modified, as will be described below. The scanner 22 includes a plurality of x-ray sources 24, of which three are shown by way of example, and a plurality of x-ray detectors 26, of which three are shown by way of example. The sources 24 and the detectors 26 are held in their respective positions by a frame 28 which encircles a subject 30 which is typically a living creature such as a human being or an animal. The sources 24 and the detectors 26 are positioned symmetrically about the subject 30, and are connected electrically to a controller 32 which includes circuitry. In particular, it is noted that each of the sources 24 is connected by two electric lines to the controller 32, a first of the lines 34 providing an electric signal which activates the source 24, and a second of the electric lines 36 providing an electric signal which modulates the x-ray beam at a predetermined modulation frequency. The detectors 26 are connected by electric lines 38 to the controller 32 for inputting data about detected radiation to the controller 32.

FIG. 2 (figure 2 of '006 patent) shows details in the construction of one of the sources 24, as well as components of the controller 32, and an interconnection between the controller 32 and one of the detectors 26. All of the sources 24 function in the same manner, and all of the detectors 26 function in the same manner. The x-ray source 24 comprises a target 40 rotated by a motor 42, and a collimator 44. The collimator is positioned along a path of x-rays emanating from the target 40 for defining an x-ray beam 46 directed towards the subject 30. The source 24 further comprises an electron gun 48 which includes a filament

strike the target 40 to generate the x-rays, the process of generation of the x-rays being well-known. A battery 56 connected between the target 40 and the filament 50 symbolically illustrates electric potential in the range of thousands of volts applied between the target 40 and the filaments 50. Electric potential for the electrode assembly 52 is provided from a bias voltage source 58 within the controller 32, the voltage of the source 58 being coupled to the electrode assembly 52 via a switch 60 also located within the controller 32.

The x-ray source 24 further comprises a klystron 62 of which two cavities 64 and 66 are shown in longitudinal sectional view, the cavity 64 being located between the cavity 66 and the electrode assembly 52. The central axis of the klystron 62 coincides with an axis of the electron beam 54. The beam 54 passes through an aperture 68 in an end wall 70 of the cavity 64, a tubular region 72 interconnecting the cavities 64 and 66, and an aperture 74 in an end wall 76 of the cavity 66. A probe 78 in the form of a loop is located in the cavity 64 for receiving inputted microwave power. Microwave power is provided by way of a microwave signal generated within a microwave source 80 located within the controller 32, the microwave signal being coupled from the source 80 to the probe 78 via a switch 82 also located within the controller 32.

Also included within the controller 32 is a computer 84, a frequency selector 86, an analog-to-digital converter 88 and a switch 90. Signals from a detector 26 are coupled by

the switch 90 to the converter 88, the converter 88 converting the analog signals of the detector to digitally formatted signals to be inputted to the computer 84.

FIG. 3 (figure 6 of the '006 patent) illustrates a basic radiotherapy method. The procedure begins with a modulation of the x-ray beam with the microwave signal. The beam is directed upon the subject and the microwave modulating signal is swept in frequency.

The radiation propagating from the x-ray source and through the subject is detected. This is followed by a recording of the frequencies at which absorption of radiant energy occurs. After this information has been obtained, the x-ray beam is modulated at a specific frequency for which absorption has been noted. Then, the beam while modulated at the specific absorption, or resonant, frequency is directed at the subject for irradiating the subject. Photon energy is transferred to macromolecules within the subject for destruction of the macromolecules. Where the macromolecules represent a malignancy, the procedure of the invention destroys the malignancy without damaging neighboring tissue.

The following prior art describe known initial therapeutic achievements and frequency specific biological effects of microwaves

1. Frequency Specific Absorption by DNA, RNA, Protein and Invivo

Webb and Booth³ performed microwave spectroscopy on DNA, RNA, protein, and

bacteria, showing individual frequency-specific absorption peaks for each substance

which correspond to those of intact cells, with the intensity of absorption at each peak

being proportional to the relative proportion of those substances in the cell.

WO 2004/000414 PCT/US2003/019410

Furthermore, there were frequency specific effects on growth rate of the cells, all corresponding with absorption peaks in the spectra (those of DNA inhibiting growth, those of RNA at one peak inhibiting and at one stimulating growth).

- In a review for the Naval Research Institute, Glaser and Dodge¹⁹ reported that microwaves between 40 and 150 GHz were found to selectively interfere with the synthesis of DNA and protein, and that the effect appeared to be frequency dependent.

 Lower frequencies did not show nonthermal mutagenic effects.
- 10 2. Differential Absorption By Tumors At Specific Frequencies

Webb⁴, using laser-Raman spectroscopy, demonstrated that tumor cells absorb
microwaves at specific frequencies not absorbed by normal cells and could selectively
alter the metabolism of tumor cells in a non-thermal manner by exposure to
frequencies harmless to normal cells, all effects being frequency specific.

15

20

3. Narrow Resonant Effects of Microwaves on Growth of Cells

Grundler and Keilmann⁵ found that microwaves influence the growth of yeast with a surprisingly strong frequency dependence, with resonance as narrow as 8 megahertz, confirming the existence of a non-thermal resonant microwave sensitivity in cells.

- The sharp frequency dependence and effect at low intensity of radiation are indicative of a non-thermal action⁶. Webb and Dodds¹⁸ also detected decreased growth of E.

 Coli with 136 GCmicrowaves.
- 4. Frequency Specific Genetic and Viral Destruction

Mickey and colleagues⁷ demonstrated non-thermal biological effects of high frequency radio waves, including frequency-specific killing of viruses and microorganisms without affecting the host, genetic changes at specific loci, chromosomal aberrations, lethal mutations, and frequency specific denaturation.

5

A Soviet study²⁰ using millimeter waves was reported to show maximal effect peaking at 6,5 MM., resulting in decreased viral infective activity, increased phage activity. Cell wall disruption, protoplasmic degeneration, altered red blood cell stability, altered nucleic acid and protein concentration, and effects on hematopoiesis and liver cell nuclei and mitochondria.

Viral multiplication in mammalian cells was affected by microwaves as a result of changes in nucleic acid and protein synthesis, resulting in lowered multiplication of herpes virus in infected cells, as reported by Luczak, et al¹⁷.

15

10

5. Selective Destruction of Tumor By Microwaves

West and Regelson⁸ noted reduction in tumor size and significantly reduced viability of lung tumor cells and leukemia cells with no lethality of normal embryo cells at low levels of pulsed nonthermal irradiation at 27.12 MHz.

20

6. Specific Microwave Effects on Chromosomes and DNA

Baranski and Czersk⁹ noted chromosomal effects and influence of microwave radiation on mitosis, with depressed cell proliferation and chromosomal despirilization, a picture never seen in ionizing radiation induced damage. They felt

this indicated with high probability that molecular effects that influence the spatial structure, energy levels, and consequently, the biological and metabolic activity of macromolecules are responsible for these effects in contrast to electrical field changes. Optical Density studies by Varma and Traboulay¹⁴ showed DNA strand separation in the GHz range of microwave non-ionizing radiation.

Together, these studies indicate that the frequencies of resonant absorption decrease with increasing molecular size, 100 MHz affecting T-RNA, while millimeter waves affect macromolecular proteins, for example. Similar effects were noted by Revzin and Neumann¹², who detected conformation changes in ribosomal-RNA using pulsed MHz radiation, with changes in orientation of the entire RNA molecule concomitant with helix coil transitions of oligomeric base-pair regions, suggesting restructuring of units the size of genes or their transcripts.

15 7. Mechanism of Action of Microwaves on DNA

Considering the interaction of electromagnetic energy with living systems in the light of quantum effects, Baranski and Czersk⁹ note that if the photon energy of irradiation corresponds to quantum differences among the various possible energetic states of a molecule, a quantum of energy may be absorbed and excitation of the molecule occurs. Return to the unexcited state may take place by energy transfer by rearrangements within the molecule. Thus, fluctuations from the equilibrium distribution of tertiary structure (e.g. denaturation) are expected.

8. Enhanced Effect Of X-Rays Combined With Microwaves

5

10

Averbach, et al¹³, observed decreased growth of E. Coli bacteria at specific microwave frequencies of 70.5 and 73 GHz and reported on a possible interaction with X-rays.

Mickey and Colleagues⁷ showed that microwave-range waves acting in conjunction with Gamma rays are far more mutagenic than either type of radiation alone.

Frequency specific effects of microwave radiation have been described by Klainer and Frazer¹⁰ by Raman spectroscopy, and in a review by Frolich¹¹ describing resonant effects on growth of bacteria, yeast, viruses, protein, metabolism, and alterations in the effects of x-rays on bone marrow.

- 9. Some characteristics of the glutathione cycle revealed by ionizing and non-ionizing electromagnetic radiation.
- Holt JA, Med Hypotheses 1995 Oct;45(4):345-68 Microwave Therapy Centre, West Perth, Australia.

The cyclic reaction of GSH-->GSSG-->GSH (designated R(exp) or R(e)) obeys the three specific features of life by producing energy in exponential quantities relative to time, is in effect irreversible and is inherited from generation to generation. In multicellular life, this reaction produces the energy for mitosis and is kept in controlled inactivity until needed to maintain perfection of form and function by energizing mitosis. The immediate control of Re appears to be feedback process-dependent on the concentration of GSSG. Ultra high-frequency electromagnetic radiation of 434 MHz (UHF) will change Re from inactive to active and, in so doing,

10

WO 2004/000414 PCT/US2003/019410

it causes resonance and/or fluorescence of the glutathione cycle which changes its radio sensitivity. Re is the primary direct target of ionizing radiation and produces the energy for mitosis. Clinical observations suggest that, in the normal cell, Re is inactive and is not killed by 3 x 2700 rads or 6 x 1650 rads yet, when active, its sensitivity value (DO) is approximately 160 rads. Using the standard radiobiological equation of response to ionizing radiation, it can be deduced that radiosensitive cancers have two or three Re units active per cell and radio resistance increases in proportion to the number of potentially active Re units per cell. Re appears to be the main cause of cancers' increased conductivity of electricity compared with normal tissue. In cancer therapy, UHF is the best radiosensitiser ever discovered (up to two or more decades). Re is also intelligent compared with non-exponential reactions but cannot be the basis of intellectual brain functions which must be based on non-electrical chemical processes.

PMID: 8577298 [PubMed - indexed for MEDLINE]

Bibliography

- 1. Datta, Jl. American Medical Association 271:800('94).
- 20 [Microwaves with x-rays to treat malignant brain tumors.]
 - 2. Beardsley, T.A. A War Not Won. Scientific American Jan. '94:130

 [Lack of significant improvement in overall cancer demise rate]

5

10

Webb, S. & Booth A. Absorption of Microwaves by Microorganisms. Nature
 222:1199-1200 ('69)

[Frequency selective-DNA]

- Webb, S.J. Effects of Microwaves on Normal and Tumor Cells as Seen by Laser-Raman Spectroscopy. J. Microwave Power 11:138 '76.
- Grundler, W. and Keilman, F. Physical Review Letters. 51:1214 '83
 [Strong frequency dependence on yeast prove nonthermal resonant microwave sensitivity
 in biology.]
 - Gandhi, o. Ed. Biological Effects and Medical Applications of Electromagnetic Energy. PP. 380-2. 90. Frequency Specific Effects.
- 7. Mickey, G.H. Electromagnetism and Its Effect on the Organism. NY State J.

 Medicine 63:1935-42('63)

[Frequency specific killing of viruses without affecting the host; chromosomal mutation]

- 8. West, B. and Regelson, W. Pulsed Radio Wave Effects on Tumor Growth, J.
- 20 Microwave Power 11:176-7('76)

[Non-thermal selective]

- Baranski, S. and Czersk, Biological Effects of Microwaves. 70-71, 132-4'76.
 Chromosomal Effects. Possible Genetic Effects and Influence of Microwave Radiation on Mitosis. Cellular Effects.
- 5 10. Klainer, S. and Frazer, J. Raman Spectroscopy of Molecular Species During Exposure to 100 MHz Radio-Frequency Fields. Ann NY ACAD Sci. 323-6('74) [Frequency effects on T-RNA]
- 11. Frohlich, H. The Biological Effects of Microwaves. Adv. Electron and Electron
 Physics 53:127-50('80)
 [Frequency specific effects on bacteria, yeast, viruses, protein metabolism, bone marrow,

and Raman spectral absorption.]

- 12. Revzin, A. And Neumann, E. Conformation Changes in R-RNA Induced by [1
 MHz] Electric Impulses. Biophys. Chem. 2:144-50('74).
 - 13. Averbeck, D. Et al. Microwave [inter] Action in Cells With X-ray. J. Microwave

 Power 11:143 ('76)
- 20 14. Varma, M. and Raboulay. DNA Studies in Measuring Mutagenicity Caused by Non-Ionizing Radiation. *Mutation Res*:31:386-92('75)
 - Greenebaum, V. Et al. Long-Term Effects of Weak 45-75HZ EM Fields on the Slime Mold. Technical Report, U. Wisconsin('75)

- 16. Mittler, S. Non-Thermal Radiowaves and Genetic Damage in Drosophila, Proc. IEEE, 6th Annual Meeting, Miami Beach.
- 5 17. Luczak, M. ET Al. Effect of Microwaves on Virus Multiplication in Mammalian Cells. J. Microwave Power 11:173-4('76)
 - 18. Webb, S. and Dodds, D. Inhibition of Bacterial Cell Growth by 136 GC Microwaves, Nature 218:374-5 ('68).
 - 19. Glaser, Z.R. Biomedical Aspects of Radio Frequency and Microwave Radiation.

 Science Policy Research Division, Lib. Congress
- 20. Sevastyanova, L. and Potapov. Resonance Effect in Biological Action of Microwave
 Radiation. *IEEF Symposium*, ('76)
 - 21. Schliepake, Erwin, The Medical Use of Electrical High Frequencies. English Translation of 2nd German Edition by R. King Brown, Actinic Press, London: '35
- 20 22. Karzmark, C.J. Advances in Linear Accelerator Design for Radiotherapy, Medical Physics 11:2,105-128, '84.
 - 23. Nonthermal Effects Of Microwave Radiation On Mammalian Cells: Experimental And Theoretical Results. Stephen F. Cleary, Ph.D., Bioelectromagnetic Laboratory,

Department of Physiology and Biophysics, Medical College of Virginia, Virginia Commonwealth University, Richmond, Virginia 23298.

The precise degree of experimental control afforded by in vitro exposure systems has permitted investigation of direct cell physiological responses to microwave radiation under nonthermal exposure conditions. A variety of cellular alterations have been attributed to nonthermal microwave interactions. Such effects include: 1) altered cation transport and binding; 2) ion channel kinetic changes; 3) biochemical alterations; 4) effects on the mitotic cycle; and 5) modulation of cell proliferation and transformation.

Whereas such effects are generally consistent with microwave-induced alteration of signal transductive pathways at the membrane surface detailed mechanistic has been elusive. Recent theoretical studies indicate spatially nonuniform microwave energy absorption on cell membrane surfaces due to field coupling with cell membrane bound water molecules. Predictions based on this interaction model will be described together with supporting experimental data derived from studies of microwave and radiofrequency radiation effects on cytokine/ receptor binding.

SUMMARY OF THE INVENTION

The present invention discloses a number of new uses for the method of Cyrulnik, which can be summarized into the following categories:

MEDICAL DIAGNOSTIC CAPABILITIES - at low energy levels, the
method of Cyrulnik may be extended to be used as a sophisticated medical
diagnosis tool. The present invention discloses uses focused on localizing and

imaging a variety of biological and chemical systems and conditions for further characterization rather than for destruction;

TREATMENT OF SPECIFIC PATHOLOGICAL CONDITIONS - several
new therapeutic uses have developed with advances in medical knowledge.
The present application discloses, for example, new methods of use directed
treatment of infectious diseases, treatment of general medical diseases such as
atherosclerosis and autoimmune diseases, storage diseases, and genetic
therapy;

10

- NON-INVASIVE SURGERY provides a truly non-invasive method of eliminating unwanted tissue anywhere in the body, effectively allowing noninvasive surgery;
- REGENERATION OF CELLS AND TISSUES Selective
 destruction/activation of specific cells allows for regeneration of cells and
 tissues, such as spinal cord regeneration.

BRIEF DESCRIPTION OF THE DRAWINGS

- Figure 1 illustrates a prior art diagrammatic view of a CT scanner modified for microwave modulation;
 - Figure 2 illustrates a prior art system for microwave modulation;
 - Figure 3 illustrates a prior art process for radiotherapy using the device of figure 2;
 - Figure 4 illustrates sequential frequency modulation at each target for time-locked retrieval;

WO 2004/000414 PCT/US2003/019410

Figure 5 illustrates frequency-specific absorption and destruction of phage virus by RF MW, and

Figures 6a-6d, collectively, illustrate a method for rapid reconstruction of the CT image, by selecting the scan that is generated specifically at the frequency uniquely absorbed by a pathological entity (such as a tumor) and not at other frequencies of modulation.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

While this invention is illustrated and described in a preferred embodiment, the device may be produced in many different configurations, forms and materials. There is depicted in the drawings, and will herein be described in detail, a preferred embodiment of the invention, with the understanding that the present disclosure is to be considered as an exemplification of the principles of the invention and the associated functional specifications for its construction and is not intended to limit the invention to the embodiment illustrated. Those skilled in the art will envision many other possible variations within the scope of the present invention.

Throughout the specification and claims, the preferred frequencies used are generally cited in the microwave range, however, other frequency ranges may be used without departing from the scope of the present invention. For example, viral matter may respond better to RF frequencies. In addition, the examples cite the invention practiced using a CT device on a patient, however, other configurations providing the modulated x-ray input may be practiced and samples may be used as a source of cell or tissues without departing from the scope of the present invention. Thus, the invention is equivalently applied to blood, tissue, and/or micro arrays (e.g., DNA, protein, etc.).

The present invention is used in various embodiments to locate, diagnose and treat many specified cells and tissues, so as to provide the capability for effectively imaging, performing noninvasive surgery, and treatment of a wide variety of medical diseases and ailments.

5

The approach is empirical, in that treatment can be performed even on conditions whose precise cause is still being determined, such as atherosclerotic narrowing of coronary and cerebral arteries.

The present invention is practiced on a MM ScannerTM (a modified CT scanner whose ordinary x-ray beam is modulated in the microwave frequency range by a device known as a klystron). The use of an electron beam fast CT Scanner represents a preferred implementation of the device, although other functional equivalents and future equivalents may be used without departing from the scope of the present invention. The system has the non-linear effect of imposing a component of microwave or RF frequency in the radiation by turning the beam of electrons generating the x-rays on and off at frequencies which are calculated to be selectively absorbed by large (macro) molecules such as the DNA and their RNA transcripts which make up the genes responsible for cell growth. Since each such type of molecule has its own unique signature of electrons orbiting it, an abnormal gene or similar substance, is expected to absorb the modulated beam selectively at some particular frequency of modulation, with negligible absorption by normal molecules, much as a signal on a TV carrier wave is picked up by a circuit tuned to one particular channel. This arrangement allows for delivery of radiation to the abnormal entity, with no significant harm to normal tissue. The present invention can

also be effective for entities that cannot be imaged as a solid mass, such as viral particles and leukemic cell DNA. One embodiment being the use of micro arrays of DNA/RNA or proteins, and another being comparing patient's blood cell absorption after relapse, if any, to previous absorption profile. This might also apply to getting a library of known

frequencies of absorption by specific pathological entities, such as the abnormal storage material in Parkinson's disease and probably Alzheimer's disease, by comparing absorption profiles in such patient's with those of normal control subjects.

Figure 5 illustrates frequency selective destruction of virus (phage) inhabiting living cells (E. Coli) without harming the host cell. The frequency was swept from 15 to 40 Megacycles per second in steps of 0.1 Mc/sec. At 35.5 Mc/sec. There is strong destruction of the virus and, conversely, marked survival of the host cells.

The great advantage of this method over conventional radiotherapy results from its selectivity: whereas standard radiotherapy is markedly limited by the concomitant destruction of normal tissue, (as is also the case for virtually all known forms of chemotherapy), there is little concern for such side: effects with the MM scannerTM, resulting in both tremendously enhanced safety and effectiveness, and the promise of a cure.

20

15

CT Scanning is used in this technique for a number of reasons:

(1) It localizes the site of origin of the entity absorbing the modulated beam, allowing direct imaging thereof, revealing its nature and location

- (2) An abnormality can be visualized entirely in isolation from any other tissue, confirming its selective absorption
- (3) Since CT divides the x-ray beam into many small parts, a minute dose of radiation can be administered safely in this initial detection process which nevertheless, because of its selective absorption, permits imaging of the absorbing tissue
- (4) Since multiple scans at different microwave frequencies of modulation are imaged, a rapid scanner is advantageous, and has the additional virtue of eliminating the problem of over-heating the target in the x-ray tube with current tube design, and
- (5) Empirical Determination of the absorptive curative frequency is extremely rapid compared to biochemical and immunological paradigms to find selective effects.

Initially, a minute dosage of microwave modulation is applied to the CT scan beam, calculated to be sufficient to image the target tissue without harming normal tissue. An empirical iterative series of such images zeroes in on the frequency of selective absorption.

Adjusting the parameters and paradigm of modulation, such as decreasing the amplitude of modulation in square wave fashion without completely turning off the electron beam, can be used to provide continuous x-ray energy in addition to the modulated form, for enhancing demodulation and focusing. A similar virtually continuous x-ray beam, which is nevertheless modulated, can be formed by using two klystrons such that one turns the electron beam on while the other turns it off, and vice-versa, with arbitrary interval between them. Focusing can also be enhanced with focusing coils, which may correct defocusing.

15

WO 2004/000414 PCT/US2003/019410 27

If a rapid CT scanner is used, the frequency of the modulating microwave can be swept through arbitrarily small bands in stepwise fashion at each target, allowing retrieval of a complete scan at each frequency band by interrogating the detectors for absorption at, and only at, the precise delay after the start of modulation which that given frequency band was incident. (In a typical scan with total time of 100 milliseconds, each of the thousand targets of an ebt scanner has a nominal dwell time of 100 microseconds, allowing 3 cycles of (10⁵) frequency bands of 3 gigacycle waves [(10⁻⁹)(10⁵)=(10⁻⁴)seconds] to be sequenced. Therefore, at 1 gigacycle, 30,000 candidate frequency bands could each be used to create a scan, which as shown in the original patent, would suffice for imaging because of greatly enhanced absorption at the resonant frequency). This would allow interrogation for absorption of the transcribed DNA of the entire human genome.

Figure 4 shows a method of sweeping the microwave frequency modulating the electron beam generating the x-rays at each target of an array of identical x-ray targets. The modulating frequency is varied sequentially in selected steps over the desired range, illustrated here as from 1 to 3 gigacyles per second. A scan can be generated by specifying the time delay from onset of modulation to the time that a specified frequency was operant, and using that time delay at

each detector to construct a CT scan resulting from modulation at that frequency only.

20

10

To facilitate reconstruction of the scans for reasonable throughput, the software need only compare one or a small number of pixels inside the known area of interest (e.g., tumor) with a similar number outside, since a complete scan is only needed at the frequency where there is absorption in the tumor but not outside, which would be not

more than about 1- 10 frequencies, corresponding to the abnormal genes in the tumor.

Therefore, the time to reconstruct two single scans in the unmodulated mode with (512²)

= 36,000 pixels would be the same as comparing the above-mentioned pixels, two for each frequency, for the 30,000 frequencies tested. Throughput would thus be on the order of taking 1 diagnostic rapid scan, 2 for each allele plus one for mutation, and one therapeutic irradiation at full duty cycle (at least 8 reconstructs and 6 comparisons), for a total of about 2 minutes.

DIAGNOSTIC CAPABILITIES:

or superior to state-of-the-art MRI spectroscopy. Thus: (a) target macromolecules are imaged without confounding artifact, and their nature can be determined directly by comparison with known frequencies of absorption of the various known macromolecules without use of injected dyes, (b) entire systems of cell types are visualized in extended distribution, such as functional distributed groups of neurons producing or having receptors for various neurotransmitters or the distribution of cells carrying a certain antigen or receptor, and (c) specific normal and abnormal cells and materials are detected and can be isolated. Therefore, detection of the presence of an abnormal gene, for example, in an individual becomes relatively simple and definitive, as a rapid alternative to more intricate methods of genetic screening in current use, and (d) the detection of diseases such as Alzheimer plaques and tangles, or herpes simplex virus are only a few examples of the diagnostic power of this technique in obtaining information that would replace invasive procedures such as brain biopsy or PCR amplification of spinal fluid,

currently needed for definitive diagnosis of these conditions having no definite biological marker on laboratory testing.

Figures 6a-6d, collectively, illustrate a method for selectively reconstructing only the image which shows the pathological entity alone that absorbs the modulated x-rays uniquely at one of several frequencies of modulation. Figures 6a-6c illustrate scenarios for frequencies that do not provide absorption by a pathological entity only. Figure 6a shows non-absorption (white pixels) in both tumor and brain tissues; 6b shows absorption (black pixel) by the brain, but not the tumor (white pixel); 6c shows absorption by both brain and tumor (both black pixels). Figure 6d illustrates the correct frequency of modulation and corresponding desired imaging, aborption by the tumor (black pixel), but not the healthy brain tissue (white pixel). This method: (a) confirms that there is absorption of the modulated x-rays by the pathological entity and not by normal structures; (b) identifies the frequency of modulation that is absorbed only by the pathological entity, as is determined by ascertaining the time delay from the beginning of modulation, as noted in figure 4, at which this imaged scan was generated; (c) makes throughput time reasonably short by not reconstructing images in which there is absorption by normal structures, and/or not by the pathological entity.

20

Specific diagnosing applications include, but are not limited to:

- Transmissible spongiform encephalopathy (mad cow disease) currently, to detect this disease in animals, which can be transmitted to humans by ingesting their meat, examination of their brains is required, resulting in the loss of significant numbers of normal cattle since the prolonged incubation period of the responsible abnormal prior protein precludes early clinical detection. Selective absorption of radiation by the abnormal prion would allow imaging with this device as a non-invasive biological marker with tremendous public health benefits as well as great savings to the cattle industry.
- Security screening current methods of screening baggage and passengers boarding commercial vehicles or entering large gatherings of people rely on metal detection or on x-ray imaging of baggage using the shape of visualized objects for identification. A much more accurate identification could be made by the MM scanner since the nature or composition of the scanned object would be identified. For example, since each substance is made of unique molecules, a container filled with explosives would light up at a frequency of modulation that a container of the same shape containing a harmless substance would not. Similarly, an envelope containing anthrax bacilli would be easily differentiated from other mail.
- Selectively destroying pathogens in media entering other "clean"
 environments, including blood and blood products for transfusion
 - Military applications:

5

10

15

- O Biological Warfare while counter-measures to some diseases that could cause mass casualties exist, they are able to be circumvented by genetic engineering. For example, it is known that the Soviet Union produced strains of germs that are engineered genetically to be resistant to current therapies, be they antibiotics or vaccines.

 Since the MM scanner detects the frequency that a particular agent absorbs as it exists at the time of use, genetic engineering would pose no obstacle to being able to eradicate the new strain.
- o Microwave modulation of x-rays permits irradiation to selectively absorbing targets that is orders of magnitude greater than conventional radiation, yet need not be focused, since there is relatively negligible absorption of other objects and materials in the same field. Thus, selected entities with known imaging characteristics could be destroyed without harming-people for example. This could be applied with minute screening doses at checkpoints with high suspicion of terrorists (with little harm to people) to detect concealed explosives.

TREATMENT OF SPECIFIC PATHOLOGICAL CONDITIONS:

- Other applications include, but are not limited to, treatment of other pathological conditions involving large molecules, such as:
 - Atherosclerotic occlusion of arteries causing heart attack and stroke, can be
 treated noninvasively by this technique at the time of initial imaging of the acute

episode since the clot consists of a macromolecular conglomeration that can be non-invasively destroyed by selective absorption of the microwave modulated radiation.

- Experimental evidence already supports frequency selective destruction of viruses and bacteria in this region of the spectrum, although a system for in vivo delivery of the radiation was not available hitherto as is now the case with the MM ScannerTM
- AIDS and other viral diseases including but not limited to Ebola, Smallpox,
 SARS, hepatitis, encephalitis, meningitis, and influenza and endocarditis.
- 10 Autoimmune diseases including, but not limited to, rheumatoid arthritis, diabetes, collagen vascular diseases, Guillain-Barre's disease, chronic inflammatory neuropathies, Crohn's disease, ulcerative colitis, asthma, allergic rhinitis, glomerulonephritis, organ transplant rejection, graft versus host disease, allergic encephalomyelitis, post-viral encephalitis, and thyroiditis. A number of diseases 15 in which the body reacts against its own tissue have resisted cure and remain chronic, such as arthritis, and, as recently noted, diabetes. While immunosuppressive drugs exist, they are generally toxic because they are nonspecific, altering the entire immune system. The MM ScannerTM, however, would have a selective effect on the macromolecular complexes involved or on 20 their genetic precursors and cells of origin, offering the possibility of prevention or cure. Since the target need not be in a single physical locus, disease progression itself may be halted as well as elimination of offending autoantibodies in active lesions. (Monoclonal antibodies have limited

33

effectiveness in these cases because they are either destroyed as foreign to the patient's immune system or too humanized to recognize human antibodies as foreign.

- Malaria, which is, on a world-wide basis, the greatest killer.
- Tuberculosis and other Mycobacterial infections
 - · Leprosy, which require years or lifelong treatment with medication
 - Fungal infections whose systemic treatment carries a significant risk of serious
 side effects
 - Bacterial Diseases which are resistant to drugs as well as those whose rapid
 detection would be extremely important, such as anthrax
 - Post-Viral diseases, for which, in general, there are no available medications,
 such as acute disseminated encephalomyelitis, Dawson's post-measles and post-influenza encephalitis
 - Genetically engineered resistant organisms, such as smallpox virus, known to have been designed to resist current immunization, and anthrax rendered resistant to antibiotics
 - Prion diseases including but not limited to Jacob-Creutzfeld disease in humans
 and spongiform encephalopathy in animals
 - Chronic or disseminated infectious diseases such as Lyme disease, syphilis and other spirochetal diseases, and ricketsial diseases.

10

15

- Atherosclerosis, which narrows the arterial supply to vital structures such as the brain and heart, is the number one killer in the U.S. Despite the myriad of research on this condition, there is no known cure. Current management is quite invasive, consisting of open heart bypass grafting, or a number of less invasive procedures on these vital organs, such as angioplasty of various types. These atherosclerotic plaques are distinctive structures containing specific types of cells and large molecular collections such as phospholipids and cholesterol. As such, they would be expected to absorb microwave modulated radiation selectively. This can be easily determined by CT visualization in the MM ScannerTM, which would indicate the ability to eliminate the plaque or its progression. Moreover, this could be done noninvasively both for focal narrowing as well as diffuse disease, including sites inaccessible to invasive techniques such as surgery and angioplasty
- The ability of the MM ScannerTM to target selectively an abnormal gene offers the exciting possibility of being able to modify the transmission of inherited diseases: by eliminating those germ cells carrying the abnormal gene, it would be possible to render the affected parent-free of any germ (reproductive) cells carrying the abnormality. To minimize ethical concerns and to offer a single therapeutic session, this would best be done prior to conception. Even if the gene is dominant, a parent carrying it has a 50% chance of having normal offspring, but currently there is no other way known to eliminate the other 50% possibility of an affected child, short of either sterilization or abortion, and that after intricate and invasive genetic testing procedures on the fetus.

5

10

15

To eliminate the gene in individuals already affected by an inherited disease, such as Huntington's Chorea (in which initially normal appearing people develop severe mental deterioration and uncontrollable movements in middle life), one would have to target all of their cells, or at least those in the affected organ (the brain in this case). Since only certain systems of neurons appear to be affected, it is possible that the abnormal gene is only activated in certain cells, offering the possibility that selective irradiation of these abnormal genetic transcripts by the MM ScannerTM may halt or cure the disease.

In various diseases such as Alzheimer's, Parkinson's, Jacob Creutzfeld & other storage diseases, an abnormal material accumulates in the tissues which correlate with the pathological manifestations of the disease. Whether this is due to an abnormal gene product or lack thereof, as in the case of hereditary forms of these diseases, or a sporadic defect, that results in an abnormally truncated peptide or protein that then forms macromolecular aggregates, or to a pathological isoform that then induces formation of a cascade of macromolecular sheets of the abnormal isoform as in prion diseases, diagnosis and treatment of these conditions can be accomplished by detecting the pathological material using microwave modulated x-rays at characteristic frequencies, with CT scanning using microwave modulated x-rays to detect characteristic distributions of the pathological material, for diagnosis, and irradiating at increased duty cycle to destroy the pathological material. This would halt the progression of these diseases and may reverse the death of those cells not yet irreversibly damaged.

5

10

15

The destruction of pathogens with the MM ScannerTM is one of the likeliest applications for several reasons:

These microbes are foreign organisms with great probability of significant difference in frequency of absorption than human nucleic acid. Obviously, where antimicrobial medication is available or the disease is self-limited (such as the common cold), this application would be limited.

NON-INVASIVE SURGERY:

The present invention use of the MM ScannerTM provides a truly non-invasive method

of eliminating unwanted tissue anywhere in the body, effectively allowing non-invasive surgery.

Specific non-invasive surgery applications include, but are not limited to:

- Bile acids around which gallstones develop may form large enough
 conglomerates of molecules to respond to the range of frequencies in the
 microwave range, allowing the possibility of their dissolution by the MM
 ScannerTM, and eliminating the need for another very common operation
 (cholecystectomy).
- One of the most common operations in neurosurgery and in orthopedics consists
 of removal of a herniated intervertebral disc. Non-invasive alternatives to this procedure have been desperately sought, as is attested to by the popularity of the attempt to treat this condition with chymopapin injections into the disc (itself invasive and dangerous because of allergic reactions to the injected enzyme),

and the literature is replete with cases of failed back operations. Since the disc material consists of a gel-like conglomerate of large macromolecules, the MM ScannerTM has the potential to destroy selectively the offending disc material in a totally non-invasive fashion.

- Surgery is often done to remove tissue that is otherwise normal but which is
 pathologically excessive, such as in the case of nerve entrapment syndromes,
 where fibrous tissue builds up as a result of repetitive trauma (often
 occupational) and compresses an adjacent nerve. Localized irradiation of this
 tissue with the MM ScannerTM could reverse this process by stopping the
 continued overgrowth of these connective tissue cells
 - Hearing loss due to otosclerosis, the most common cause of heredity deafness, is due to overgrowth of bone in the middle ear. Stopping this process with the MM ScannerTM, by selectively de-immortalizing the growing bone cells in this region could be another widespread application of this technology.
- Not all abnormal cells that should be eliminated are growing, but their pathological nature is likely to be reflected in their macromolecular makeup, whether genetically inherited or due to direct damage that is passed on to daughter cells as a somatic mutation, or present as an injury in common to a group of cells (e.g., affecting their macromolecular membranes). For example, foci of abnormal cells producing epilepsy are now able to be removed surgically after being imaged by PET scan. If the abnormal focus is imaged by the MM ScannerTM it could be eliminated non-invasively without surgery
 - Whereas surgery is not applicable to generalized epilepsy, selective absorption
 of modulated radiation would, in fact, apply to a diffuse system of cells, such as

5

10

15

those involved in non-focal epilepsy, as well as in dvskinesias, ectopic tissue such as glandular tissue (e.g. excess thyroid) and endometriosis, sarcoid and xanthomata, to name a few, allowing noninvasive cure

Disenabling of a functioning system is also sometimes performed surgically, such as lesioning the spinal pain tracts in cases of intractable pain. This could be accomplished non-invasively by selective destruction of systems of sensory cells that can be imaged using the MM ScannerTM

REGENERATION OF CELLS AND TISSUES:

10

15

20

5

Other applications include, but are not limited to, regeneration of cells and tissues.

It is now known that it injured spinal cord does not regenerate because certain cells secrete substances in the lesion preventing regrowth. Selective destruction of these cells or the DNA/RNA transcripts of the genes that produce these inhibitory molecules should allow for regeneration. The myelinated tracts of the spinal cord, unlike peripheral nerves, do not regenerate despite intact cell bodies proximal to the lesion and, in many cases, anatomical continuity of the scaffolding connecting these to the lower motor or sensory neurons more distally. Recent studies have determined that this is due to the presence of inhibitory molecules on the myelin sheaths surrounding the nerve fibers that otherwise could grow back. The modulated microwave x-rays have the potential to non-invasively destroy these molecules either as they exist in the macromolecular myelin sheath or at the stage of DNA transcription in the oligodendrocytes that produce them. In the case of

PCT/US2003/019410 WO 2004/000414 39

> totally transected cord requiring insertion of scaffolding, such as with stem cells, a preliminary step is still required in which the inhibiting myelin or its contained macromolecules is destroyed, a step that could still be done as described noninvasively with minimal damage to non-inhibitory tissue

The cloning of an entire organism with its component tissues from a the set of genes of a somatic differentiated cell, as well as the production of differentiated cells from stem cells, which have already been accomplished, indicates that the genetic machinery, the genome, which is the same in the nuclei of all cells of an individual, contains the entire program for sequentially reproducing the processes of differentiation.

To start the process, or to enter the program at any point, it is simply needed to supply the proper environment to turn on that set of genes by re-creating the external conditions that exist when the cell is at that stage of differentiation: for a whole organism, one inserts the somatic nuclear DNA into an enucleated egg cell; for producing T cell receptors, the stem cell is incubated with white blood cells. This capability of the environment surrounding the DNA to turn it on at any desired point, after which it will go through the entire subsequent sequence of steps in the program of differentiation, implies that there are transcription factors available to the DNA to carry out that series of steps, provided that an initial reaction occurs of a chemical nature, such as the binding to the DNA of the transcription factor that starts the program at that particular step. The nature of the process that triggers such binding, without which differentiation does not occur despite the availability of the

5

10

15

transcription factors to the DNA, currently is empirical and not well understood.

When two molecules bind together, they enter into a combined state whose energy level is lower than before the reaction. To make this happen, it is often necessary to supply energy, such as heat, which raises the energy level of the molecules from which they can subsequently fall when they combine; without the temporarily added energy, the molecules remain separate entities even if in close proximity. Since heat will supply energy in a non-specific way to all the reactants present, many molecular species will bind to each other when heat is supplied, precluding a precise triggering reaction to start the program of differentiation. When electromagnetic energy is absorbed, however, no free energy is produced as a byproduct, allowing precise delivery of exactly the amount of energy needed to change the configuration of the reacting species to the new combination product. In other words, the delivery of electromagnetic energy that is selectively absorbed by potentially binding molecules will trigger their reacting with each other. In the case of macromolecules such as DNA, the frequencies absorbed are in the microwave range. The precise amount of energy needed the trigger the program to start by binding a transcription factor to the DNA can be delivered by controlling the frequency of the microwaves, since the energy of electromagnetic waves is locked to their frequency. By empirically determining which frequencies are being absorbed by cells that are the step-wise process of differentiation, a means of driving the initial reaction that starts the

5

10

15

growth and differentiation program can be realized. By detecting such frequencies in vivo and supply them to a particular tissue, regeneration will proceed.

CONCLUSION

A system and method has been shown in the above embodiments for the effective implementation of a system and method for diagnosing and interacting with selected specific entities containing or comprised of macromolecules. While various preferred embodiments have been shown and described, it will be understood that there is no intent to limit the invention by such disclosure, but rather, it is intended to cover all modifications and alternate constructions falling within the spirit and scope of the invention, as defined in the appended claims. In fact, this technique should work no matter how target molecules differ from normal cells, and does not depend on oncogenes per se: it simply detects at which frequency the entity containing or comprised of the target molecules, but not non-target molecules, absorb the radiation, whether due to oncogenes, greater amounts of macromolecules, higher levels of protein synthesis or metabolism, or morphological, physical or chemical differences. The specific frequency range should not be limited to microwaves, but include any frequency range which interacts with a target medium as per the present application.

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

□ BLACK BORDERS
□ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
□ FADED TEXT OR DRAWING
□ BLURRED OR ILLEGIBLE TEXT OR DRAWING
□ SKEWED/SLANTED IMAGES
□ COLOR OR BLACK AND WHITE PHOTOGRAPHS
□ GRAY SCALE DOCUMENTS
□ LINES OR MARKS ON ORIGINAL DOCUMENT
□ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

☐ OTHER: ______

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.